



NOTES:

- CENTERLINE OF MOUNTING HOLE OF UPPER AND LOWER RETAINERS ALIGNED WITHIN 2'.
- DO NOT INFLATE TO MORE THAN 6.9 bar WITHOUT GOODYEAR APPROVAL.
- FASTENER TORQUE NOT TO EXCEED 27 N-m.
- ASSEMBLY TO BE SUPPORTED, TOP AND BOTTOM, BY MINIMUM 140mm DIAMETER PLATE. EXTERNAL LIMITS MUST BE PROVIDED IN MOUNTING STRUCTURE TO PREVENT SPRING FROM EXCEEDING MIN AND MAX HEIGHTS.
- COLLAR HATS TO BE ALIGNED WITH BLIND TAPS AND AIR FITTING.

6	COLLAR HAT	579-92-9-195	2
5	BLANK LABEL	579-08-9-114	1
4	STEEL CLAMP RING	ASB-08-4-023	2
3	UPPER RETAINER	ASC-92-8-282	1
2	LOWER RETAINER	ASC-92-6-083	1
1	FLEXIBLE MEMBER	579-92-3-530	1
ITEM	NAME	DRAWING NO./SPEC. NO.	REQD

BILL OF MATERIAL

▽ INDICATES A KEY CRITICAL CHARACTERISTIC (KCC), WHICH MUST CONFORM TO GMS VI-010

THE GOODYEAR TIRE & RUBBER COMPANY GREEN OHIO

4. This drawing and its contents are the property of Goodyear Tire & Rubber Company. It is to be used only for the specific purpose for which it was prepared and is not to be distributed or reproduced in any form without the written consent of Goodyear Tire & Rubber Company.

HMA/NCIP 2/26/99 DEPT NO.021
 288-850 METRIC AIRSPRING ASSEMBLY
 579-92-2-850

TELEPHONE: 614/885-5000 FAX: 614/885-5001
 UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETERS
 ANGLES IN DEGREES
 X ± 0.05
 XX ± 0.02
 XXX ± 0.01

1 REV. 10/88/ENCL 8/09/00
 2 REV. 10/88/ENCL 8/09/00
 3 REV. 10/88/ENCL 8/09/00
 4 REV. 10/88/ENCL 8/09/00
 5 REV. 10/88/ENCL 8/09/00
 6 REV. 10/88/ENCL 8/09/00

REVISED:

NOTE: DRAWING MAY NOT BE
 PLOTTED TO SCALE