



FS 200-10

CONTI® Single Convolution Air Spring



FS 200-10



Force-height diagram

Purchase order data

Type	Order No.
Rubber bellows only	60319
With clamped plates G 3/4 air inlet 38.1 mm excentrical	2681 045 000
With clamped plates G 1/4 air inlet 44.5 mm excentrical	60030
With clamped plates G 1/4 air inlet 44.5 mm excentrical with bumper	2681 047 000

Additional types on request



Service instructions
 M8 = 25 Nm
 G 3/4 = 50 Nm
 G 1/4 = 25 Nm

Technical data

Min. pressure	0 bar
Return force to min. height	≤ 200 N
Overall weight with clamped plates	2.3 kg

Vibration isolation - dynamic characteristic values

Design height H: recommended 110mm, minimum 90mm

Pressure p [bar]	3	4	5	6	7	8	Vol. V[l]
Force (Load) [kN]	5.5	7.5	9.6	11.9	14.0	15.7	2.7
Spring rate [N/cm]	1500	2050	2600	3150	3700	4250	
Natural frequency [Hz]	2.6	2.6	2.6	2.6	2.6	2.6	

Pneumatic application - static characteristic values

Force F [kN]	Pressure p [bar]	3	4	5	6	7	8	Vol.[l]
Height H [mm]	120	4.5	6.2	8.2	10.4	12.1	13.8	2.8
	110	5.5	7.5	9.6	11.9	14.0	15.7	2.7
	100	6.3	8.6	11.0	13.4	15.5	17.5	2.3
	90	7.0	9.4	12.1	14.6	17.0	19.2	2.2
	80	7.6	10.2	13.0	15.7	18.2	20.6	1.8
	70	8.1	10.9	13.6	16.5	19.3	21.9	1.6
	60	8.5	11.3	14.2	17.1	20.1	23.0	1.3